



Model No. CL610

Part No. 13-6002-010

DATASHEET

APPLICATION

- Bars, Pubs, Clubs
- Entertainment Venues,
- Theatres
- Houses of Worships,

Key Features

- 2-way bi-amplified, bass-reflex design
- 260 mm (10") custom woofer with 64 mm (2.5") voice coil, 34mm (1.4") Exit throat.
- Frequency response from 65Hz to 20kHz
- HI-CUT/DRUM-FILL, LO-CUT/DOUBLE, FOH, VOCAL, TOURING) 90° conical dispersion
- 35 mm (1.38") stand socket, two integrated handles and optional wall mount bracket
- Compact vented band pass Biamp design Enclosure
- 2 x XLR connectors
- Available in black Textured Finish



Product Description

- The DAT 1x10" woofer and 1.4" compression driver Active Monitor system. The DAT CL610 has met the following performance criteria. The frequency response of 65-20000Hz & frequency sensitivity of 96 dB, Maximum SPL of 119dB, The CL610 features 15mm birch plywood construction covered in a scratch resistant black or white paint with two pocket handles. The rear facing input panel provides XLR with Loop,

Model	CL610
Code	13-6002-010
Type	Two Way Full Range System
Frequency Response	65Hz-20kHz±3dB
Power handling	300W(RMS)1200W(PEAK)
Sensitivity	96dB(1W@1M)
Max SPL	119dB(PEAK/1M)
Drivers	LF 10"(260mm) woofer 65mm(2.5in)coil HF 1.4"compression driver with 34mm titanium diaphragm
Nominal impedance	8 ohm
Coverage	90°H×50°V
Finish	Textured paint
Connectors	2X XLR Connectors
Enclosure	Plywood
Dimensions	325×492×306mm(W×H×D)
Packing Dimensions	385×595×410mm(W×H×D)/0.08cbm
Net weight	15kg(CV-102C) 15.5kg (CV-102CP)
Gross weight	16.5kg(CV-102C) 17.5kg(CV-102CP)