



Model No. CL612

Part No. 13-6002-012

DATASHEET

APPLICATION

- Bars, Pubs, Clubs
- Entertainment Venues,
- Theatres
- Houses of Worships,

Key Features

- 2-way bi-amplified, bass-reflex design
- 260 mm (12") custom woofer with 64 mm (2.5") voice coil, 34mm HF 1.75" Compression drive
- Frequency response from 55Hz to 18kHz
- HI-CUT/DRUM-FILL, LO-CUT/DOUBLE, FOH, VOCAL, TOURING) 90° conical dispersion
- 35 mm (1.38") stand socket, two integrated handles and optional wall mount bracket
- Compact vented band pass Biamp design Enclosure
- 2 x Speakon connectors
- Available in black Textured Finish



Product Description

- The DAT 1x12" woofer and 1.75" compression driver Active Monitor system. The DAT CL612 has met the following performance criteria. The frequency response of 55-18000Hz & frequency sensitivity of 98 dB, Maximum SPL of 126dB, The CL612 features 15mm birch plywood construction covered in a scratch resistant black or white paint with two pocket handles.

Model	CL612
Code	13-6002-012
Type	Two Way Full Range System
Frequency Response	55Hz-18kHz±3dB
Power handling	400W(RMS)1600W(PEAK)
Sensitivity	98dB(1W@1M)
Max SPL	126dB(PEAK/1M)
Drivers	LF 12"(310 mm) woofer 75mm(3in)coil HF 1.75"compression driver with 44mm titanium diaphragm
Nominal impedance	8 ohm
Coverage	60°H×40°V
Finish	Textured paint
Connectors	2X XLR Connectors
Enclosure	Plywood
Dimensions	376×632×397mm(W×H×D)
Packing Dimensions	455×710×495mm(W×H×D)/0.14cbm
Net weight	23.5kg
Gross weight	26 kg