



Model No.DM122A

Part No. 17-4002-012

DATASHEET

APPLICATION

- Bars, Pubs, Clubs
- Entertainment Venues,
- Theatres
- Houses of Worships,

Key Features

- 2-way bi-amplified, bass-reflex design
- 380 mm (12") coaxial custom woofer with 64 mm (2.5") voice coil, 25mm (1") Exit throat B&C with 44mm (1.7") voice coil
- Frequency response from 50Hz to 20kHz
- HI-CUT/DRUM-FILL, LO-CUT/DOUBLE, FOH, VOCAL, TOURING) 90° conical dispersion
- 35 mm (1.38") stand socket, two integrated handles and optional wall mount bracket
- Compact vented band pass Biamp design Enclosure
- 2 x XLR connectors
- Available in black Textured Finish



Product Description

- The DAT 1x12" woofer and 1.75" compression driver Active Monitor system. The DAT DM122A has met the following performance criteria. The frequency response of 55-20000Hz & frequency sensitivity of 95 dB, Maximum SPL of 123dB, The DAT DM122A features 15mm birch plywood construction covered in a scratch resistant black or white paint with two pocket handles. The rear facing input panel provides XLR with Loop, RCA ST

Model	DM122A
Code	17-3002-12
Type	Monitor system
Frequency Response	55Hz-20kHz±3dB
Power handling	400W(RMS)1600W(PEAK)
Sensitivity	95dB(1W@1M)
Max SPL	123dB(PEAK/1M)
Drivers	LF 12"(310mm) woofer 75mm(3in)coil HF 1.75"compression driver with 44mm titanium diaphragm
Nominal impedance	8 ohm
Coverage	80°H×60°V
Finish	Textured paint
Connectors	2X XLR Connectors
Enclosure	Plywood
Dimensions	650×340×480mm(W×H×D)
Packing Dimensions	730×435×535mm(W×H×D)/0.16cbm
Net weight	23kg(CV-122M) 24.5kg (CV-122MP)
Gross weight	26.5kg(CV-122M) 27.5kg(CV-122MP)

