



Model No.DM152A

Part No. 17-4002-015

DATASHEET

APPLICATION

- Bars, Pubs, Clubs
- Entertainment Venues,
- Theatres
- Houses of Worships,

Key Features

- 2-way bi-amplified, bass-reflex design
- 380 mm (15") coaxial custom woofer with 64 mm (2.5") voice coil, 25mm (1") Exit throat B&C with 44mm (1.7") voice coil
- Frequency response from 50Hz to 20kHz
- DSP with 6 factory presets (ORIG, HI-CUT/DRUM-FILL, LO-CUT/DOUBLE, FOH, VOCAL, TO 90° conical dispersion
- 35 mm (1.38") stand socket, two integrated handles and optional wall mount bracket
- Compact vented band pass Biamp design Enclosure
- 2 x XLR connectors
- Available in black Textured Finish



Product Description

- The DAT 1x15" Active Monitor system. The DAT DM152 has met the following performance criteria. The frequency response of 50-500Hz & frequency sensitivity of 102 dB, Maximum SPL of 132dB, 1000W recommended amplifier. The DAT SW1000 features 18mm birch plywood construction covered in a scratch resistant black or white paint with two pocket handles. The rear facing input panel provides XLR with Loop, RCA ST

Code:
17-4002-015

Configuration:	2 way
Built-in amplifier LF/HF:	400/80 W RMS
Built-in amplifier peak LF/HF:	800/160 W
Frequency response:	55Hz - 20KHz -/+3dB
Low Frequency woofer:	15 - 3 coil inch
High Frequency driver:	1 - 1.7 coil inch
Maximum SPL cont/peak:	127/133 dB
AC Power requirements:	240 / 110 V AC
Input connector:	XLR with loop, RCA ST
Power cord:	5/16.4 m/ft
Net Dimension (WxHxD):	632x354x516 / 24.9x11.9x20.3 mm/inch
Net Weight:	21.3/46.9 kg/lb
Transport Dimension (WxHxD):	732x454x616 / 28.8x17.9x24.2 mm/inch
Transport Weight:	25.8/56.9 kg/lb