



Model No. **SW1600P2**

Part No. **19-1600-215**

## DATASHEET –SW1600P2 SUBWOOFER SYSTEM

### APPLICATION

- Bars, Pubs, Restaurants,
- Retail shops, Clubs
- Entertainment Venues,
- Fitness center
- Theatres
- Houses of Worships
- Exhibition Centers

### Key Features

- Passive Sub-woofer system
- 0.75" birch plywood cabinet
- 2x 15" custom made woofers
- 1600W RMS recommended amplifier
- Max SPL 126dB peak
- Four pocket handles
- 2 x Speakon NL-4 connectors
- Available in black or Brown extra texture paint



### Product Description

The subwoofer SW1600P2 is a high performance sub-bass system designed for large scale venues including touring and fixed installations. It features with two 800 watt 15" (380mm) driver units with magnet structure and suspension engineered for maximum linear excursion. Its two woofers are housed in bandpass box with bass horn loading to deliver ultra-powerful bass energy. The SW1600P2 extends low-bass response and high efficiency is required from a relatively compact enclosure. In addition, SW1600P2 is ideal for fixed sound installations such as discos, nightclubs, halls, conference centers and commercial events.

## SUBWOOFER TECHNICAL PARAMETERS

Model	CV-215C & CV-215CP(Active)
Type	Dual-drivers sub-bass system
Frequency Response	42Hz-500Hz±3dB
Power handling	1600W(RMS) 6400W(PEAK)
Sensitivity	101dB(1W@1M)
Max SPL	133dB(PEAK/1M)
Drivers	2×15"(380mm) woofer 100mm(4in)coil
Nominal impedance	4 ohm
Finish	Textured paint
Connectors	2×NL4MP speakon
Enclosure	Plywood
Dimensions	880×556×732(W×H×D)
Packing Dimensions	970×645×830mm(W×H×D)/0.49cbm
Net weight	75kg
Gross weight	80kg