

## APPLICATIONS

- Conference Rooms
- Exhibition Canters
- Houses of Worship
- Entertain Venues
- Auditorium
- Hotel Ballroom



## SYSTEM DESCRIPTION

- The OTO 44DN Audio Matrix Shall Consist of 4 CH Mic /Line Local input and 4 CH Local audio Output , Standard 4 CH Dante Input slot / input gain can be switched, Audio channels, where the resources of the Dante channels and analog channels can be shared, can be switched channels
- All input and output channels with independent phase curve adjustment function, PEQ type selection phase shift can be phase 180 degree phase adjustment, 2 phase shift can be 360 degree phase curve adjustment
- Standard Dante slot machine with 4 local inputs and 4 local outputs
- Dante Standard Digital Network with 4 inputs and 4 outputs
- Dante Standard Digital Network with 4 inputs and 4 outputs
  - Each analog input channel has a +48 V phantom power
  - Microphone and linear input gain can be switched
  - The sensitivity of the microphone input can be adjusted.
  - Input channel processing section includes low cut
  - Feedback suppression
  - Parametric equalization
  - Noise gate,
  - Gain Control
  - Mute function for Each Channel
  - Phase linked adjustment, Volume grouping adjustment and other
  - Front panel with input and output level indicator, USB, power, network port