

**PAMP- 202DN**

- 2x 20 watts Amplifier
- Bluetooth
- 2x stereo Input
- 70/100 volt output
- LAN / Local Input

APPLICATIONS

The terminal Amplifier **DAT PAMP-202DN** is for IP public address system, with backup source function, mainly used for campus paging, suitable for school, office building, factory workshop, meeting room places etc.

- Conference Rooms / Meeting Room / School Paging
- Exhibition Canters
- Commercial Paging
- Distributed Audio

SYSTEM DESCRIPTION

The DAT **PAMP- 202DN** is a flexible wall mountable small in size Amplifier with 2 x analog IN/ 2x Digital Input (LAN) 2x analog OUT.100 volt (constant Volt) output

Function characteristics

1. Metal frame, convenient for hanging.
2. capable for Remote Controlling.
3. Build-in 2x20W amplifier, and tone quality reaches CD level.
4. Supporting internet broadcasting, disk broadcasting and local broadcasting (AUX in, Microphone input,).
5. 70V /100V analog broadcast can be connected as backup, when internet offline by accident, the backup broadcast would seamlessly play.
7. Bluetooth module could be a choice for wireless local broadcast and long distance broadcast.

Technical parameters

input Power	DC 24V
Output Rated Power	2x20W(1KHz@0dB)
Input Sensitivity	750mV/10K Ω
SNR	Local \geq 75dB Network \geq 75dB Bluetooth \geq 65dB
THD	\leq 0.3%(@1W)
Frequency Response	Local/network:40Hz~20KHz Bluetooth/backup : 200Hz~7KHz
Network Communication Protocol	ARP, UDP, TCP/IP, ICMP, IGMP.
Audio bitrate rate	8Kbps~320Kbps
Sampling Rate	8K~48KHz
Audio Format	MP3

MBps	10/100Mbps
Input Voltage	≤50ms
Working Temperature	-10°C~ +60°C
Storage Temperature	-20°C~ +80°C
Working Humidity	10%~90%
Size	250×163×42(mm)
Weight	2.5Kg

What's in the box?

- o 1 x DAT –PAMP202
- o 1 x 12VDC universal power supply (90~240VAC)
- o 1 x Shielded USB cable (1.5m)

Dante Model Available on Jun 2018