



Model No. **SW100P**

Part No. 19-1000-018

## DATASHEET

---

### APPLICATION

- Bars, Pubs, Restaurants, Retail shops, Clubs
- Entertainment Venues, Fitness center
- Conference Rooms, Theatres
- Houses of Worships, Exhibition Centers

### Key Features

- Passive subwoofer
- Compact vented band pass subwoofer design Enclosure
- 460 mm (18") custom "FaitalPro" neodymium Magnet High excursion woofer with 75 mm (3") voice coil
- Frequency response from 36Hz to 100Hz
- 18mm birch plywood cabinet
- Eight M10 fly points, M20 top mount stand socket and two FBT design aluminum handles
- 1X18" custom made high excursion woofers
- 1200W RMS recommended amplifier
- Max SPL 132dB peak
- Two pocket handles
- 2 x Speakon NL-4 connectors
- Available in black or white extra texture paint



### Product Description

The DAT **SW1000P** 1x18" passive Subwoofer system. The DAT **SW1000** has met the following performance criteria. The frequency response of 50-500Hz & frequency sensitivity of 102 dB, Maximum SPL of 132dB, 1000W recommended amplifier. The DAT SW1000 features 18mm birch plywood construction covered in a scratch resistant black or white paint with two pocket handles. The rear facing input panel provides 2 x Neutrik NL4 speakon female connectors

Model	SW1000P
Type	Subwoofer System
Frequency Response	50Hz-500Hz±3dB
Power handling	1000 Watts
Sensitivity	102dB(1W@1M)
Max SPL	132dB(PEAK/1M)
Drivers	1×18"(460mm) woofer 100mm(4in)coil
System Peak	2000 watts
Color	Black
Nominal impedance	8 ohm
Coverage	60°H×40°V
Finish	Textured paint
Connectors	2×NL4MP speakon
Enclosure	Plywood
Dimensions	580×700×735(W×H×D)
Packing Dimensions	660×795×810mm(W×H×D)/0.40cbm
Net weight	50kg(CV-181C) 52kg (CV-181CP)
Gross weight	55kg(CV-181C) 57kg (CV-181CP)