



Model No. **CL312**

Part No. 13-3002-012

APPLICATION

- Bars, Pubs, Restaurants, Retail shops, Clubs
- Entertainment Venues, Fitness center
- Conference Rooms, Theatres
- Houses of Worships, Exhibition Centers

Key Features

- Passive 2 Way Speaker
- 0.5" birch plywood cabinet
- 1x 12" custom made woofers
- 600W RMS recommended amplifier
- Max SPL 126dB peak
- Two pocket handles
- 2 x Speakon NL-4 connectors
- Available in black or Brown extra texture paint



Product Description

The DAT **CL312** 1x12" two way passive sound reinforcement speakers. The DAT **CL312** has met the following performance criteria. The frequency response of 50-3000Hz & frequency sensitivity of 97.3dB, Maximum SPL of 126dB, 600W recommended amplifier. The DAT CL312 features 0.59" birch plywood construction covered in a scratch resistant black or white paint with two pocket handles. The rear facing input panel provides 2 x Neutrik NL4 speakon female connectors

Model	CL312P
Type	Two-way, full range system
Frequency Response	50Hz-30kHz±3dB
Power handling	600W(RMS)1600W(PEAK)
Sensitivity	98dB(1W@1M)
Max SPL	126dB(PEAK/1M)
Drivers	LF 12"(310mm) woofer 75mm(3in)coil
	HF 1.75"compression driver with 44mm Titanium Diaphragm
Color	Black
Nominal impedance	8 ohm
Coverage	60°H×40°V
Finish	Textured paint
Connectors	2×NL4MP speakon
Enclosure	Plywood
Dimensions	376×632×397mm(W×H×D)
Packing Dimensions	455×710×495mm(W×H×D)/0.14cbm
Net weight	23.5kg
Gross weight	26kg